



easyCharge

Just Park and Go!

 **INTIS**

READY FOR YOUR APPLICATION

Cities



park and charge



READY FOR YOUR APPLICATION

Hotels



service excellence




READY FOR YOUR APPLICATION

Logistics



optimising productivity



wireless charging

User-friendly charging - just park and go



Indoors & outdoors

Suitable for indoor and outdoor installation



Battery-saving

Intelligent charging for enhanced battery longevity



App compatible

Connected mobility with remote condition monitoring

ADVANTAGES:

- ▶ no cables, no connectors to break ▶ robust ▶ maintenance free ▶ simple to integrate ▶ invisible
- ▶ automated ▶ battery lifetime saving ▶ reliable ▶ scalable ▶ efficient
- ▶ modular ▶ convenient ▶ extended mileage ▶ economically to operate ▶ competitive with smaller batteries
- ▶ supporting smart grid implementations ▶ extended usage of renewable energy ▶ First CE certified charging platform

Wireless charging for your e-scooter application

INTIS easyCharge - the new inductive platform allows easy charging for your e-scooter. Charging is hands-free and fully automatic - just park and go.

Cooperation partners INTIS and Metz have succeeded in bringing the world's first inductively charged e-scooter model Metz moover to market. Other e-scooters with this technology will be available soon.

INTIS easyCharge - enabling electric and shared micro mobility to be more convenient, more environmentally friendly and more cost effective.



Platform in porcelain stoneware material on stainless steel frame



Platform in GRP GiRo material with stainless steel panels

	easyCharge 1
Number of charge points	1 per platform
Charging power [W]	Up to 100
Grid connection	Household power socket
Grid voltage [VAC]	90-264
Grid frequency [Hz]	47-63
Usage area	Indoors/outdoors
WPT-operating frequency [kHz]	85
EV-communication	Infrared
Charging data communications	Ethernet/ LAN
Charging time [hours]	EV-Battery capacity [Wh] / Power load [W]
Material	Porcelain stoneware plate on stainless steel frame or GRP GiRo with stainless steel panels
Dimensions [mm]	
Width:	600
Length:	1186
Height front:	105
Height rear:	38
Weight [kg]	approx. 25

Powered by INTIS

www.intis.de/micromobility.html

Contact:

Catia Hilgart

catia.hilgart@intis.de

Driven by Metz

www.metz-moover.de/en/induction/

